










	Warranty	10 years*
	Composition	83% vinyl - 7% fiberglass - 10% PET
	Backing	Vinyl + Felt
	Total thickness	ISO 1765 5mm - 0.20"
	Total weight	ISO 8543 3000 g/m ² - 88.5 oz/yd ²
	Roll width	EN ISO 24341 ca. 200cm - ca. 6'7"
	Roll length	EN ISO 24341 ca. 30m - 32.8 yd
	Tile size 16 pcs per box	EN 994 50cm x 50cm - 19.69" x 19.69"
	Level of Use	EN 1307 ASTM D5252 Class 33 Heavy commercial use
	Foot traffic test	ASTM D6119-12 Heavy traffic
	Castor chair suitability	EN 985 Continuous use
	Reaction to fire	EN 13501-1 Bfl-s1
	Critical radiant flux	ASTM E648-15e1 NFPA 0,84 W/cm ² Class I
	Smoke density	ASTM E622 < 300
	Walking test	ISO 6356 AATCC 134-2006 < 2 kv Permanently antistatic
	Light fastness	ISO 105-B02 ≥ 7
	Slip resistance	EN 13893 ASTM C1028-07 DIN 51130 EM 13036-4 ≥ 0,3 0,85 R9 65
	Impact sound reduction	ISO 10140 19dB
	Acoustical absorption	ISO 354 αw = 0,15
	Walking noise reduction	EPLF 021029-3 SL70
	Dimensional stability	EN 986 ISO 2551 Meets the requirements
	Thermal resistance	ISO 8302 Suitable for underfloor heating
	CE Certificate	EN 14041 0493-CPR-0151

 **Environment, health and safety**

Recycled Content	10%
Reach	Compliant
LEED v4	Compliant (LEED Contributing Product)
CDPH Standard Method V1.2	Pass
BREEAM International	Compliant
BREEAM[®] NOR	Pass
French VOC Regulation	A+ Certified
French CMR components	Pass
AGBB/ABG	Pass
Belgian VOC Regulation	Pass
Indoor Air Comfort Gold	Pass
Blue Angel (RAL UZ120)	Pass
EN 717-1	E1
M1 Protocol of July 2017	Pass
Plasticizer Content	Phthalate Free**



Co² neutral on demand

* Terms and conditions are available on request

** Standard from 09/2018